## **D-XLR**

- Solid Metal Body Construction
- Rugged Plastic Belt Clip
- Adapts 48v to 3v PIP (Plug In Power)
- Works with standard 3.5mm microphones

The D-XLR can convert 12-48V Phantom Power down to 3V 'Plug in Power', which allows microphones with 3.5mm TRS connectors to run off Phantom Power. The D-XLR is specially designed for the Deity V-Series of microphones to trigger their Smart 3.5mm TRRS outputs with PIP from a standard XLR.

At the same time, D-XLR has no adverse effect on microphones like the V-Mic D3 PRO in terms of signal-to-noise ratio, total harmonic distortion and sensitivity like another model on the market. D-XLR uses a 3.5mm TRS standard wired input\* that is gold-plated so that contacts on the plug make a better connection and does not loosen.

\*Will not work with 3.5mm lavaliers wired for Sony UWP.

## **Compatible Microphones**

- •A.Lav
- •V.Lav
- •V-Mic D3
- •V-Mic D3 Pro+
- •Other 3.5 Standard TS/TRS Microphones

## **Specifications**

Weight:29.2g

Dimensions: 69.7mmH x 19mmW x 19mmD

Voltage: 12-48V Phantom

Bias Voltage: 3V SNR: 80.9dB THD: 0%

Input: 3.5mm Standard TRS

Output: 3 Pin XLR Metal: CNC Aluminum